Copyright © 2015 by MultiOne Srl. All rights reserved. No part of this publication may be reproduced, distribulted, or transmitted in any form or by any means. The information and images in this document are provided for illustrative purposes only and do not bind the manufacturer, who reserved. No part of this publication may be reproduced, distribulted, or transmitted in any form or by any means. The information and images in this document are

SNOW PLOW

http://tiny.cc/snowplow1



• 5 configurations

This versatile, hydraulically operated snow plow offers 5 different blade operating positions:

- 30° right
- 30° left
- Straight
- Scoop
- V-plow

The plow controls features on-the-go fingertip adjustments to plow through the deepest snow.

Equipped with shock absorbing springs that allow the blade to trip forward when an obstacle is encountered, saving wear and tear on the blade and MultiOne.

TYPE	А	В	С	D	Е	F	G	н	Kg.	L/min.	Press. max (bar)
170	1465	1545	1465	1545	1550	1610	1380	1480	350	10/15	200
230	1980	2065	1980	2065	2065	2125	1900	2000	420	10/15	200



Model	Blades Width	Blades height	Slewing angle	Weight	Code	Price					
150-170	150-170 cm (59-67 in)	29.5 in (75 cm)	±30°	350 kg (772 lbs)	C891300						
200-230	200-230 cm (78.7-90.5 in)	29.5 in (75 cm)	±30°	420 kg (926 lbs)	C891310						
Accessories											
	Code	Price									
Floating Adapte	C891320										
Extension Wings	C891325										



